
Stencil Documentation

Release 2.0.2

Curtis Maloney

Sep 01, 2023

Contents

1	Writing Templates	3
1.1	Expressions	3
1.2	Comments	3
1.3	Variables	4
1.4	Block Tags	4
2	Using Templates	9
2.1	From Strings	9
2.2	From a file	9
2.3	Context	10
2.4	Rendering	10
2.5	Escaping	10
3	Extending stencil	11
3.1	Tags	11
4	Why?	13

Contents:

Writing Templates

Templates are just plain text files, with special notation (called ‘tags’) to indicate where the engine should take action.

There are 3 basic types of tags:

- var
- block
- comment

1.1 Expressions

At several points in the syntax, an Expression can be used.

An expression can be:

- an integer
- a float
- a string
- an expression

All expressions start by looking up their first element in the `Context`. For example the expression `name` will look for `Context['name']`.

After that, they behave just like Python. You can do a dict or list lookup using `[]`, or call a function using `()`. Note, however, that function invocations are limited to only positional arguments.

1.2 Comments

Comment tags are discarded during parsing, and are only for the benefit of future template editors. They have no impact on rendering performance.

1.3 Variables

Var tags are used to display the values of variables. They look like this:

```
Hello {{ expr }}
```

1.4 Block Tags

Block tags perform some action, may render some output, and may “contain” other tags.

```
{% include 'another.html' %}
```

1.4.1 Built In Tags

for

The `for` tag allows you to loop over a sequence.

```
{% for x in expr %}  
...  
{% endfor %}
```

The `for` tag also support and `else` block. It will be used if sequence to be iterated is empty.

```
{% for x in empty_list %}  
...  
{% else %}  
Nothing to show.  
{% endfor %}
```

if

The `if` tag allows for simple flow control based on a truthy test.

```
{% if expr %}  
Success!  
{% endif %}
```

It also supports negative cases:

```
{% if not expr %}  
Failure!  
{% endif %}
```

And, like the `for` tag, it supports an `else` block:

```
{% if expr %}  
Success!  
{% else %}  
Failure!  
{% endif %}
```


“Truthiness” is based on the Python concept. Here are some things that are “truthy”:

- True
- non-empty strings
- non-empty lists or dicts
- non-zero values

Conversely, things that are “falsy” are:

- False
- empty strings
- 0 and 0.0
- empty lists and dicts

include

The `include` tag lets you render another template inline, using the current context.

```
{% include expr %}
```

Additionally, you can pass extra expressions to be added to the context whilst the other template is being rendered.

```
{% include form_field.html field=current_field %}
```

load

This tag lets you load other code modules to add new tags to use in this template. See [Tags](#) for more details.

```
{% load 'myproject.tags' %}
```

The value passed is a Python import path.

extends and block

The `extends` tag allows the use of template inheritance. A *base* template can denote blocks of content which can be overridden by templates which extend it.

Caution: The `extends` tag only works properly if it is the *very first* thing in your template.

Say we have the following base template:

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <title>{% block title %}Welcome!{% endblock %}</title>
    <link rel="stylesheet" type="text/css" href="/static/css/base.css">
    {% block extra_head %}{% endblock %}
  </head>
  <body>
```

(continues on next page)

(continued from previous page)

```
<header>
  <h1>{% block header %}Welcome!{% endblock %}</h1>
</header>
<main>
  {% block content %}{% endblock %}
</main>
<footer>
  <p>&copy; 2016 Me!</p>
</footer>
  {% block footer_scripts %}{% endblock %}
</body>
</html>
```

Now, when rendered itself, it will show as:

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <title>Welcome!</title>
    <link rel="stylesheet" type="text/css" href="/static/css/base.css">

  </head>
  <body>
    <header>
      <h1>Welcome!</h1>
    </header>
    <main>

    </main>
    <footer>
      <p>&copy; 2016 Me!</p>
    </footer>

  </body>
</html>
```

However, if we write another template which extends this one, we just have to write now the blocks we want to override:

```
{% extends 'base.html' %}

{% block title %}My Title!{% endblock %}

{% block content %}
Welcome to my first page!
{% endblock %}
```

This will override only the two given blocks content.

Any content outside of block tags will be ignored.

with

Using `with` you can temporarily assign new values in the context from expressions. This can help avoid repeated work.

```
{% with url=make_url(page) %}  
<a href="{{ url }}" class="link {% if is_current_url(url) %}current{% endif %}">{{  
  ↳page.title }}</a>  
{% endwith %}
```

case/when

Allows switching between multiple blocks of template depending on the value of a variable.

```
{% case foo.bar %}  
{% when 1 %}  
You got one!  
{% when 2 %}  
You got two!  
{% else %}  
You got some!  
{% endcase %}
```

The optional *{% else %}* clause is used if no when cases match.

Using Templates

To use stencil templates there is very little to do.

2.1 From Strings

To build a template from a string, just create a `stencil.Template` instance:

```
>>> from stencil import Template
>>> t = Template('Hello, {{name}}!')
```

And to render it:

```
>>> t.render({'name': 'Bob'})
'Hello, Bob!'
```

2.2 From a file

First you'll need to create a `TemplateLoader`, passing it a list of paths to search for templates.

```
>>> from stencil import TemplateLoader
>>> loader = TemplateLoader(['templates/'])
```

You can ask it to load a template freshly calling `TemplateLoader.load`

```
>>> t = loader.load('base.html')
```

The `TemplateLoader` can also cache loaded, parsed templates if you treat it as a dict:

```
>>> t = loader['base.html']
# Loads template from file.
>>> s = loader['base.html']
# Returns the same template instance.
```

2.3 Context

When rendering a template, you need to pass it a `Context` - this is the limit of information the template can access. When instantiating a `Context`, you can pass it the information you want available to the template.

```
>>> ctx = stencil.Context({'a': True})
```

2.4 Rendering

Finally, to render a template, call its `render()` method, passing a context.

```
>>> output = t.render(ctx)
```

Additionally, you can pass a file-like object for the template to write into:

```
>>> with open('output.html', 'w') as fout:
...     t.render(ctx, fout)
```

2.5 Escaping

By default, all variables (e.g. `{{ var }}`) will be *escaped*, using `html.escape`.

Values can be marked as “safe”, and thus not requiring escaping, by wrapping them in `stencil.SafeStr`.

Alternatively, any object whose `__safe__` attribute is `Truthy` will not be escaped.

2.5.1 Alternate Escaping

You can override the escaping function used when constructing the `Context`.

```
>>> ctx = Context(..., escape=my_escape)
```

Stencil allows you to easily add new tags.

3.1 Tags

All tags derive from the `stencil.BlockNode` class, and self-register with `stencil` on declaration.

```
from stencil import BlockNode

class MyTag(BlockNode, name='my'): # This is matched in {% my %}
```

When `stencil` finds a tag matching this name, it will call the `BlockNode.parse` classmethod, passing it the rest of the tag content, and the template instance. This method must return a `BlockNode` sub-class instance.

```
class MyTag(BlockNode):

    @classmethod
    def parse(cls, content, parser):
        return cls(content)
```

The default action is to just return an instance of the class, passed the tag content.

When a template is rendered, a `blocks.render` method will be called, passed a `Context` instance, and a file-like object to output to.

3.1.1 Tags with children

Some tags contain *child* nodes (e.g. `for`, `if`, `block`).

To do this they build a `NodeList`:

```
class MyBlock(BlockNode):

    @classmethod
    def parse(self, content, parser):
        nodelist = parser.parse_nodelist({'endmyblock',})
        return cls(nodelist)
```

This will consume tags until it reaches one with a name found in the list. The tags are added to a `Nodelist` instance, except the matching one which it stored in `Nodelist.endnode`.

A `Nodelist` can be rendered easily by calling their `render` method, which works just like a `BlockNode`.

```
nodelist.render(context, output)
```

3.1.2 Expressions

To have an argument resolved as an expression, use the `Expression.parse()` function. This will parse then value passed, and construct an `Expression` instance.

Then in render, call the expression's `.resolve(context)` to get its value.

For more fine grained parsing, and to parse `key=expr` syntax, create an `Expression` instance:

```
expr = Expression(content)
```

This provides several useful methods:

```
value = tokens._parse()
```

Parses a single argument, be it a string, float or int literal, or a lookup.

```
kwargs = expr.parse_kwargs()
```

Parse `key=expression` sequences, and construct a dict of *key*: *Expression()* items.

CHAPTER 4

Why?

There are plenty of template engines in Python, and I've even written my own powerful, super-fast one (knights-templater), so why write another?

I was experimenting with AWS' Serverless concept, and was saddened to learn it only supports Python 2.7 currently. I wanted templating, but felt back-porting K-T to Py2 just wasn't warranted.

So I figured, why not see how small I can make a functional template language?

Apparently, "under 400 lines of code" is the answer. . .

Since then AWS Lambda picked up support for Python3, and stencil has grown considerably - in features, more than code size.